

63-3-2

MODEL Minuteman

DOCUMENT NUMBER D2-5859, Volume I

SECTION OR ADDENDUM NO. .3

TITLE

Wing III QPRI Supplement for WS-133A Minuteman Hardened and  
Dispersed.

145-60 2300 No. 0-0000 (atch)  
At Post Office Annex, TDC

CATALOGUE NO. ASTIA  
AS AD NO. 402301

NO. OF PAGES 38

DATE 20 March 1963

The technical information contained herein has been coordinated with the System Functional Analysis of System Engineering.

for E. Melich  
J. B. Marcella, Chief  
System Functional Analysis

78100  
WORK ORDER

2-5261  
UNIT NO.

52133  
ITEM NO.

PREPARED BY J. C. Clerkin

APPROVED BY R. M. Coomer W. J. Larson

APPROVED BY William H. Wetzel

APPROVED BY J. M. Barker

D. A. Cole

Sub-section title page  
Documents

PAGE 1-0.3

**402 301**

MODEL WS-133A DOCUMENT NO. D2-5859 Volume I

TITLE The Wing III QPRI Supplement for WS-133A Minuteman H&D

REVISIONS				ADDITIONS			
PAGE	DATE	PAGE	DATE	PAGE	DATE	PAGE	DATE
				1-0. 3 1. 3 thru xvii. 3 4-14. 3 4-15. 3 4-25. 3 4-26. 3 4-30. 3 thru 4-36. 3 4-39. 3 4-40. 3 5-5. 3 5-5A. 3 5-5B. 3 5-5C. 3 5-6. 3 5-7. 3 5-8. 3	3/20/63		

## INTRODUCTION

The Wing III Supplement should be used with the Wing I QPRI and the Wing II Supplement. This supplement updates the Wing I document with the Wing II Supplement to the Wing III configuration.

The major Wing III changes resulted from hardening and extending the survival period of the Launch Facility and the Launch Control Facility. An entirely new structure, the Launch Control Equipment Building, was constructed adjacent to the Capsule. It houses the equipment necessary to sustain the Capsule and the EWO capability for extended periods. Also, a hydraulic pusher was substituted for the gearcase motor. A list of Figure A changes with a brief explanation will be found on pages iv. 3 through xv. 3.

Table i-1A. 3 (Volume I) and Table i-1B.3 (Volume II) identify personnel by Air Force Specialty Code (AFSC) that are affected by equipment changes. The equipment is identified by Figure "A" number and name. The "Status" column of Table i-1A. 3 and Table i-1B. 3 show how the Duties and Tasks have changed, as follows: Changed means that Wing II Duties and Tasks have been revised for Wing III. Added signifies that the Duties and Tasks are an addition to those for Wing II. Deleted shows that the Duties and Tasks are performed in Wing II but not in Wing III.

The "Page" column in Table i-1A. 3 and Table i-1B. 3 shows the page in the Wing I and Wing II QPRI affected by changes. The suffixes A. 3, B. 3, C. 3 . . . Z. 3 added to the page number show Wing III peculiarity. (. 3). The A. B. C. . . Z. part of the suffix shows the sequential order in which pages should follow a particular page in the basic Wing I and II document. These added pages amplify existing pages or inject new material between existing pages.

Editors Note: Whenever duty/task information has been changed or added for a given AFSC, new duty/task pages have been provided which replace or supplement pages issued previously. These new duty/task pages are listed in Table i-1A. 3 to the right of the AFSC to which they apply. Whenever duty/task information has been deleted for a given AFSC, the word "Deleted" has been entered in the "Status" column and the page number on which the data is to be deleted is listed in the "Page" column of Table i-1A. 3. Because the deleted data is, in many instances, still applicable to earlier wings, and there may be other data on the page that is still current, it is suggested that a handwritten note be placed opposite the deleted data on the duty/task page to the effect that "Figure A XXXX (or Form B XX-XXXX) duties and tasks deleted for Wing III and on."

The tables in the Supplement have the same basic numbering as corresponding tables in the Wing I document and Wing II Supplement, but in addition, they have a . 3 suffix. For example; Table 5-2. 2 is a Manning Summary for Wing II and Table 5-2. 3 is a Manning Summary for Wing III.


Tables i-1A. 2 or . 3, i-1B. 2 or . 3 and 5-2B. 2 or . 3 are in the Wing II and III Supplements only. Table 5-2B. 3 shows the composition of Minuteman Mobile Maintenance Teams for Wing III. Charts 5-1. 3 and 5-2. 3 compare Wing I, II and III Team and Manning Summaries.

#### CAUTION

The QPRI and QPRI Supplements are planning documents and should not be considered as the final source of detailed procedural information.

The Technical Orders (T. O.'s) or T. O. Checklists are the official source of detailed information on the use and maintenance of Aero-Space Ground Equipment (AGE) and should be referred to for more complete and authoritative procedures.

To assist the reader in locating appropriate T. O. data, a matrix that cross references equipment Figure A numbers to T. O. numbers is provided as Appendix A-2, Volume II of Wing III Supplement to D2-5859.



20 March 1963

Volume 1

P2-5059

Page 11

## REAL PROPERTY INSTALLED EQUIPMENT (RPIE) CHANGES

1. Figure A 1209.3 - Water Control and Removal System, LF
  - a. Check valve added on the discharge line of the Sump Pump to prevent reverse flow.
2. Figure A 1210.3 - Sewage Disposal System, LCC
  - a. Add automatic/manual valves on drain and vent lines penetrating the capsule.
  - b. Add 2" floor drain in the LCEB.
  - c. Add a 3500 gallon emergency sewage overflow tank located outside the Tunnel Junction and connected to the sewage sump.
  - d. Revise the size of the sump pump in the Tunnel Junction.
- \*3. Figure A 1230.3 - Fuel System, LCSB
  - a. This Figure A now furnishes fuel for the mobile standby generator (Figure A 1437.3) instead of the standby power source (Figure A 1323.3).
  - b. Fuel quantity is now figured for a sixty day hot water supply instead of ten day for hot water and standby power.
  - c. Delete above-ground day tank, transfer pumps and low-level alarm.
4. Figure A 1241.3 - Shock Attenuation System, LCC
  - a. Increase the number of air storage cylinders at each shock isolator from one to two.
- \*5. Figure A 1242.3 - Lift, Service, LCC
  - a. Increase live load capacity from 2,000 to 6,000 pounds.
  - b. Decrease operating speed from 50 to 25 fpm.
  - c. Increase load equipment envelope from 30 x 42 x 68 to 58 wide x 114 long x 94 high.
- \*6. Figure A 1323.3 - Electrical System, LCC (Hard)
  - a. Revise electric power ground.
  - b. Revise telephone equipment ground.

\* Indicates Figure A's included in Wing III QPRI Supplement.

6

20 March 1963

Volume I

D2-5859

iv.3

IV.3

- 6. Figure A 1323.3 - Electrical System, LCC (Hard) (Cont.)**
  - a. Relocate standby engine-generator and transfer switch from LCSB to LCEB.
  - b. Change engine starting control from manual to automatic.
  - c. Change load transfer from manual to automatic.
  - d. Delete engine-shutdown for high lube oil temperature.
  - e. Add automatic engine exerciser.
  - f. Interlock engine operation with 36" Blast Valve operation.
  - g. Add power distribution within the LCEB.
  - h. Decrease standby generator capacity from 150 KW to 75 KW.
  - i. Decrease commercial power requirements from 225 kva to 130 KW with 85% PF.
  - j. Provide power for Blast Valve Control System, Figure A 1432.3.
- 7. Figure A 1324.3 -- Water Supply System, LCC**
  - a. Add shock attenuators on the water line at point of capsule penetration.
  - b. Add remote controlled (LCC Supervisory Panel) air-operated shutoff valve on water line at point of capsule penetration.
  - c. Add 3500 gallon water storage tank (TK-112) buried outside the LCEB for emergency usage. Add seven compressed air bottles and solenoid valve inside the LCEB to pressurize the tank during the survival period.
  - d. Add an emergency shutoff valve on the water line entering the LCEB. Valve is closed manually or mechanically by an upward movement of the floor.
  - e. The water treatment equipment is revised to meet conditions at the various sites.
  - f. Add a pipe with shutoff valve to supply raw water to the sewage lagoon. Note: AIO will maintain this system.
- 8. Figure A 1325.3 - Heating System, LCSB**
  - a. Reduce boiler capacity to 250,000 btu/hr.
  - b. Add chemical pot feeder to heating system.

\* Indicates Figure A's included in Wing III QPRI Supplement.

9. Figure A 1327.3 - Security System, LCC

- a. Delete exterior door to the Security Room in the LCSB.
- b. Change size of exterior door to the Access Shift Vestibule in the LCSB from 3 x 7 to 5 x 8-6.

10. Figure A 1328.3 - Fire Alarm System, LCC

- a. Add second system for LCEB with an interlock to shut down the ventilating system for the LCC.
- b. Add visual and aural signals for fire in LCEB in both LCEB and LCC.

11. Figure A 1329.3 - Electrical System, Launcher

- a. Revise number of connected circuits.
- b. Reduce commercial power requirement from 112.5 kva to 75 KW with 0.81 PF.
- c. Divide the engine-generator control panel into an engine control panel and a generator control panel, and revise instrumentation.
- d. Shock mount equipment in the LSB.
- e. Remove emergency power test contactor from IWS panel and modify power switching arrangement to delete emergency power test sequence. (Boeing must initiate this change by FCIR. Change description is part of ECP 358.)
- f. On startup of the standby diesel generator, the load is not connected until the generator output reaches given levels. These levels have been raised from 55 cps for Wing II to 60 cps on Wing III and from 80% of nominal voltage on Wing II to 90% on Wing III.

12. Figure A 1330.3 - Shock Attenuation System, LER

- a. Add shock attenuation equipment for the launcher electrical distribution panel.

13. Figure A 1331.3 - Security System, Launcher

- a. Secure personnel access covers with commercial padlocks rather than conventional hardware with keyed locksets in standard hollow steel door.

14. Figure A 1333.3 - Personnel Support Equipment, LCC

- a. Revise the equipment list to eliminate those items of a "Stock" nature (refrigerator).

- b. Include items of built-in nature (bathroom fixtures) not previously called out in any Figure A.
  - c. Revise quantities to accommodate new estimated personnel requirements.
15. Figure A 1389.3 - Heating and Ventilating System, LSB
- a. Relocate unit heater from ceiling of room to underside of shock mounted floor.
  - b. Add 10,000 cfm supply fan.
  - c. Change exhaust fan from a 3450 cfm propeller type to a 10,000 cfm centrifugal type.
  - d. Delete snow melting requirement.
- \*16. Figure A 1390.3 - Ventilating System, LCSB
- a. Delete provision for ventilating engine-generator and brine-chiller relocated to LCEB.
- \*17. Figure A 1396.3 - Monitor System, Equipment Fault, LCC
- a. Add "LCC Supervisory Panel" in LCC (Capsule) containing the following:
    - (1) Pushbutton for electric door operator between rooms 101 and 102 in the LCSB. At Wing II there is a pushbutton located separately near the inside of the blast door operating the door between rooms 104 and 105 in the LCSB.
    - (2) To display light, buzzer and silence push-button connected to the control panel on the engine-generator and the Equipment Building Alarm Panel.
    - (3) An "open-close" switch that controls a solenoid valve in the LCEB between the compressed air cylinders and the buried water storage tank.
    - (4) A display light, bell and silence push-button connected to the Fire Alarm Control Cabinet (Figure A 1328.3) located in the LCEB.
    - (5) A display light that indicates when the Tunnel Junction Blast Door is closed and locked.
    - (6) A display light and three position switch connected to the three power phases in Panel LCRA located in the LCC (Capsule) to monitor incoming power.

\* Indicates Figure A's included in Wing III QPRI Supplement.

\*17. Figure A 1396.3 - Monitor System, Equipment Fault, LCC (Cont.)

- a. (7) An "open-close" switch that controls three solenoid valves, which in turn control air-operated valves on the cold water, drain and vent lines where they enter the capsule.
- (8) An "open" pushbutton and "closed" pushbutton to provide manual control for the Shock Contactor located in the LCEB.
- b. The Equipment Room Alarm Panel located in the Equipment Room of the LCSB at Wing II is now the Equipment Building Alarm Panel located in the LCEB at Wing III and is changed as follows:
  - (1) The three display lights for the deleted second environmental control equipment have been removed.
  - (2) A display light for no (low) LCC air exhaust has been added. The type and location of monitor are not resolved.
- c. The following changes are made in the monitoring provisions of the Generator Instrument Panel:
  - (1) The panel, which is attached to the engine-generator, is now located in the LCEB rather than the LCSB.
  - (2) A visual display "Engine failure to start" has been added.
  - (3) A visual display "air intake and/or exhaust blast valves closed" has been added.
- d. Add monitor to show closed and locked condition of Tunnel Junction Blast Door, Figure A 1440.3. Indication appears on LCC Supervisory Panel.
- e. The LCC Monitor and Alarm Station at Wing II is renamed the LCSB Monitor and Alarm Station at Wing III and is changed as follows:
  - (1) The display lights (2) for the Generator Room and the Equipment Room are deleted.
  - (2) The two-way selector switch for the flood lights is deleted.
  - (3) A display light for the water treatment system is added. The monitor for this display is located on the water meter in the Water Treatment Room, LCSB.

\*18. Figure A 1405.3 - Fuel System, Launcher

- a. Increase the size of the bulk storage tank located by the LSB from 1500 to 14,300 gallons.

\* Indicates Figure A's included in Wing III QPRI Supplement.

20 March 1963

Volume I D2-5859  
viii.3

\*18. Figure A 1405.3 - Fuel System, Launcher (Cont.)

- b. Change the day tank located in the LSB from a horizontal to a vertical configuration.
- c. Add flexible connections between the bulk storage tank and the day tank.
- d. Delete the 10" inspection outlet and manway to grade on the bulk storage tank and add an 18" buried manhole.
- e. Relocate the bulk storage tank conservation vent inside the LSB.

\*19. Figure A 1436.3 - Ventilating System, LCEB

- a. This new requirement is generated by relocating the engine-generator and brine chiller from the LCSB.
- b. These provisions were formerly included in Figure A 1390.3, Ventilating System, LCSB.

\*20. Figure A 1437.3 - Electrical System, LCSB

- a. New Figure A providing for electrical distribution system in the LCSB. Figure A 1323 previously provided for the LCSB, but now provides only for the hardened structures.
- b. Provide for mobile standby generator (to be furnished by SAC) for maintaining service in the LCSB.

\*21. Figure A 1438.3 - Fuel System, LCEB

- a. Provide fuel storage for the standby engine-generator.
- b. This requirement was previously satisfied by Figure A 1230, Fuel System, LCSB.

\*22. Figure A 1439.3 - Shock Attenuation System, LCEB

- a. Provide shock floor and attenuators for the new structure, complying with Wing III shock criteria.

\*23. Figure A 1440.3 -- Blast Door Installation, LCC, Tunnel Junction

- a. Add blast door at the elevator shaft entrance to the Tunnel Junction. This door protects the equipment and space both within the Tunnel Junction and the LCEB.

\*24. Figure A 1441.3 - Shock Attenuation System, LSB

- a. This is a new requirement providing for increased shock protection of essential equipment in the LSB.

\* Indicates Figure A's included in Wing III QPRI Supplement.

\*25. Figure A 1450.3 Accumulator Set, 24-Inch Blast Valve Control

\* Indicates Figure A's included in Wing III QPRI Supplement.

20 March 1963

Volume I      D2-5859  
                  x.3

## OPERATIONAL GROUND EQUIPMENT (OGE) CHANGES

- \*1. Figure A 1211.3 - Environmental Control System, Launcher
  - a. Delete the 8" blast valve on the air duct to the LER.
  - b. Reduce the size of the make-up air duct between the LSB and the LER from 6" to 2" and add a buried serpentine coil to increase the total length.
  - c. Mount control panels in the LER on shock mounts.
  - d. Replace the blast check valves on the brine lines entering the LER with "safety heads."
  - e. Add an absolute filter to the end of the make-up air duct located in the LSB.
  - f. Redesign the shock mounting of the equipment.
  - g. Redesign the control panel to provide automatic starting and stopping with 36" blast damper operation.
- \*2. Figure A 1212.3 - Environmental Control System, LCC
  - a. Relocate the air conditioning equipment from the LCSB to the LCEB.
  - b. Add provision for automatic shutdown of the air conditioning equipment in the event of fire in the LCEB.
  - c. Add a "clean room" to enclose the air handling equipment in the LCEB.
  - d. Add a monitor to sense low exhaust air flow from the capsule.
  - e. In the SRCC configuration, replace the dual units used in Wing II with a single large-capacity chiller and air handling unit.
3. Figure A 1246.3 - Cable Assembly Set, Launch Control Facility
  - a. ECP 403 - Delete, revise, and add cables as required to accommodate changes made to mating facilities and RPIE in the LCF.
4. Figure A 1248.3 - Cable Assembly Set, Launcher
  - a. ECP 358 - Delete, revise, and add cables as required to accommodate changes made to OGE by this ECP.

\* Indicates Figure A's included in Wing III QPRI Supplement.

20 March 1963

Volume I      D2-5859  
xi.3

5. Figure A 1373.3 - Electrical Surge Arrestor, LCF

- a. ECP 401 - Change the ESA to accommodate cable conductor pair count and the hard and soft cable plant peculiar to Wing III. Add surge protection for the soft lines connected to equipment relocated to the LCEB.

6. Figure A 1374.3 - Electrical Surge Arrestor, LF

- a. ECP 401 - Revise to accommodate changes similar to those for Figure A 1373.3.

7. Figure A 1376.3 - Interconnecting Box, LCC

- a. ECP 402 - Revise wiring to accommodate new signal conductors and routing peculiar to Wing III.

8. Figure A 1377.3 - Interconnecting Box, LF

- a. ECP 402 - Revise to accommodate changes in plug and connector sizes resulting from an increase in number of signal conductors. Revise internal and shorting plug wiring to accommodate new signal conductors and routing peculiar to Wing III.

\*9. Figure A 1383 - Gear Rack Assembly, Launcher Closure

This item is deleted.

\*10. Figure A 1417.2 - Valves, Blast (8")

This item is deleted.

11. Figure A 1418.3 - Valves, Blast (24"), LCC

- a. ECP 396 - Revise to contain limit switches for indicating open and closed positions.

\*12. Figure A 1428.3 - Valves, Blast (36"), LCEB

- a. ECP 396 - Provide two new 36" valves to protect the LCEB from blast. Design the valves for hydraulic operation and provide a means for electrical interlock control for standby generators.

\*13. Figure A 1429.3 - Blast Dampers, LSB

- a. ECP 396 - Provide two new blast dampers in each LSB. Design the valves to be actuated to the closed position by overpressure alone and to reopen automatically upon return of atmospheric pressure to near normal.

\* Indicates Figure A's included in Wing III Supplement.

20 March 1963

Volume I

D2-5859

xii.3

\*14. Figure A 1432.3 - Control System Blast Valve

- a. ECP 396 - Provide a new Blast Valve Control System to power and control the blast valves installed in the LCEB and the LCC.
  - (1) The LCEB portion of the system, used to control the 36" Blast Valves, consists of a hydraulic pump and motor, reservoir, hydraulic-nitrogen accumulator and hydraulic-electrical control panel.
  - (2) The LCC portion of the system, used to control the 24" Blast Valves, consists of a hydraulic-electrical control panel, a hydraulic reservoir and a hydraulic-nitrogen accumulator. Also included, but packaged separately, is a portable hand-operated hydraulic pump with reservoir.

\*15. Figure A 1443.3 - Rail, Hydraulic Jack

- a. ECP 321 - Modify and permanently attach to the LF spron a 90 pound per yard railroad track rail with notches appropriately spaced to be compatible with Hydraulic Jack, Figure A 4640.3.

\* Indicates Figure A's included in Wing III Supplement.  
20 March 1963

Volume I D2-5859  
xiii.3

## MAINTENANCE GROUND EQUIPMENT (MGE) CHANGES

- \*1. Figure A 4105 - Gearcase-Motor, Launcher Closure
  - a. ECP 321 - This item is deleted.
- \*2. Figure A 4141 - Dolly, Gearcase-Motor
  - a. ECP 321 - This item is deleted.
- \*3. Figure A 4277 - Sling, Gearcase-Motor
  - a. ECP 321 - This item is deleted.
- \*4. Figure A 4282 - Hoist, Gearcase-Motor
  - a. ECP 321 - This item is deleted.
- 5. Figure A 4370 - Test Stand, Gearcase-Motor
  - a. ECP 321 - This item is deleted.
- 6. Figure A 4540.3 - Cable Assembly Set
  - a. ECP 450 - This Figure A will require reduced quantities to accommodate differences in hardware allocation.
- \*7. Figure A 4640.3 - Jack Kit, Hydraulic
  - a. ECP 321 - This is a new item of MGE, replacing Figure A 4105, Gearcase Motor. This new item was initiated through BSD/STL direction. As an off-the-shelf procurement, this Figure A will be controlled by a Specification Control Drawing.
- \*8. Figure A 4645.3 - Dolly, Hydraulic Jack
  - a. ECP 321 - This is a new item of MGE, replacing Figure A 4141, Dolly, Gearcase Motor. This new item will facilitate handling of the Hydraulic Jack Kit at the Launch Facility. In addition, this item will support the Hydraulic Jack Kit during transportation between the SMSB and the Launch Facility. This is to be a Boeing designed piece of equipment.
- \*9. Figure A 4646.3 - Sling, Hydraulic Jack
  - a. ECP 321 - This is a new item of Boeing designed MGE, replacing Figure A 4277, Sling, Gearcase Motor. This sling will be used to facilitate the handling of the Hydraulic Jack Kit (with Dolly) between the Launcher Apron and the transporting vehicle.

\* Indicates Figure A's included in Wing III Supplement.

20 March 1963

Volume I      D2-5859  
xiv.3

\*10. Figure A 4648.3 - Hoist, Hydraulic Jack

- a. ECP 321 - This is a new item of MGE, replacing Figure A 4282, Hoist, Gearcase Motor. This hoist will operate both on the Launcher-Closure and on the Launcher-Apron to facilitate handling of the Hydraulic Jack Kit, with Dolly. This will be a Boeing designed item.

\* Indicates Figure A's included in Wing III Supplement.  
20 March 1963

Volume I      D2-5859  
xv.3

**SUMMARY OF EQUIPMENT CHANGES FOR WING III - Volume I**

<b>AFSC</b>	<b>Subsystem/Operation Involved</b>	<b>Status</b>	<b>Page</b>
31255G	3007      Test Set, Explosive Set Circuitry	Changed	4-14.3
44250Z	1211      Blast Valves and Manual Control Components - LF 1212      Blast Valves and Manual Control Components - LCF 1241      Shock Attenuation System 1428.3     Valves, Blast, 36-Inch 1432.3     Hydraulic System, Blast Valves	Deleted Deleted Deleted Added Added	4-25 4-25 4-25 4-25.3 4-25.3
54150G	1209.3     Water Control and Removal System, Launcher 1210.3     Sewage Disposal System, LCF 1211.3     Environmental Control System, Launcher 1212.3     Environmental Control System, LCF 1230.3     Fuel System, LCSB 1241.3     Shock Attenuation System 1242.3     Service Lift, LCF 1324.3     Water Supply System, LCF 1325.3     Heating System 1330.3     Shock Attenuation System, L 1383        Gear Rack 1390.3     Ventilation System, LCSB 1417.2     Valve, Blast 8-inch 1418.3     Valve Blast, 24-Inch 1443.3     Rail, Hydraulic Pusher	Changed Changed Changed Changed Changed Changed Changed Deleted Changed Changed Deleted Changed Changed Deleted Changed Changed Changed Deleted Changed Changed Changed Added	4-30.3 4-30.3 4-30.3 4-30.3 4-30.3 4-30.3 4-31.3 4-31.A2 4-31.3 4-31.3 4-31.3 4-31.3 4-31.3 4-31.A2 4-31.3 4-31.A2 4-31.3 4-31.3 4-31.3
54250G	1209.3     Water Control and Removal System 1242.3     Service Lift, LCF 1246.3     Cable Assembly Set, LCF 1248.3     Cable Assembly Set, LF 1249        Hatch Installation System, LCF 1323.3     Electrical System, LCC 1329.3     Electrical System, LF 1389.3     Heating and Ventilating System 1396.3     Monitoring System, Equipment Fault 4105        Gearcase Motor 4166        Cable Assembly Set	Changed Changed Changed Changed Deleted Changed Changed Changed Changed Deleted Changed Changed Changed Changed Deleted Deleted	4-34.3 4-34.3 4-34.3 4-34.3 4-34 4-34.3 4-34.3 4-34.3 4-35.3 4-35.3 4-35 4-35

20 March 1963

TABLE i-1A.3

Volume I

D2-5859

xvi-3

**SUMMARY OF EQUIPMENT CHANGES FOR WING III - Volume I**

AFSC	Subsystem/Operation Involved	Status	Page
54550Y	1211.3      Environmental Control System, LF	Changed	4-39.3
	1212.3      Environmental Control System, LCF	Changed	4-39.3
	1390.3      Ventilation System LCSB	Added	4-40.3
	1436.3      Ventilation System LCEB	Added	4-40.3

20 March 1963

TABLE i-1A.3

Volume I

D2-5859

xvii -3

POSITION DEFINITION		RECOMMENDED OR AUTHORIZED AFSC
<u>POSITION NO. 5</u>	<u>POSITION TITLE</u>	<u>AFSC 31255G/75G</u>
<u>GENERAL FEATURES</u>		
<b>POSITION SUMMARY:</b>		
<p>The Ballistic Missile Checkout Equipment Specialist is responsible for the Support Base maintenance and calibration of Electronic Test Equipment such as:</p> <ul style="list-style-type: none"> <li>623 C90 Adapter Group, Test</li> <li>624 C91 Test Center, Programmer - Fault Locator</li> <li>717.2 Test Set, Photo-Electronic Collimator</li> <li>3007 Test Set, Explosive Set Circuitry</li> <li>3013 Test Set, Command Control Console</li> <li>3092 Test Set, Programmer Group</li> <li>4012 Test Set, Sensitive Command Network</li> <li>4018 Test Adapter C91</li> <li>4152.2 Test Equipment, Electronic Facility, Base Maintenance</li> <li>4490 Missile Simulator</li> <li>4489 Message Generator</li> <li>10709 C153 Test Set, Missile Control Group</li> </ul>		
<p>The Ballistic Missile Checkout Equipment Specialist is responsible for troubleshooting and repairing interconnecting circuits of the Sensitive Command Network, Security System, Programmer Group, and Command Control Console when returned to the Support Base.</p>		

20 March 1963

Volume I

D2-5859  
4-14.3

1C

POSITION DEFINITION		RECOMMENDED OR AUTHORIZED AFSC
POSITION NO. <u>5</u>	POSITION TITLE Ballistic Missile Checkout Equipment Specialist/Technician	AFSC 31255G/75G
POSITION SUMMARY: (Cont.)		
Checkout and testing is accomplished using self test features of programmed checkout equipment, and by using standard voltmeters, frequency meters, oscilloscopes and hand tools.		
ENVIRONMENT:		
Work Location: The Ballistic Missile Checkout Equipment Specialist's duty location is in the Maintenance Branch - Electronic Section at the Support Base.		
Lines of Supervision: He will be supervised at the Support Base by the Missile Officer, AFSC 3124G.		
QUALIFICATIONS:		
The Ballistic Missile Checkout Equipment Specialist is required to perform at a low to high perceptual skill level (high level is required for test, visual inspection, function checkout, and repair of test equipment); high judgmental skill level is required for accomplishing all detailed electronic maintenance functions; motor skill demands range from high to low.		
Task performance is generally critical to subsystem operation.		
RELATION TO EXISTING AIR FORCE SPECIALTIES:		
This position type falls within the scope of AFS Ballistic Missile Checkout Equipment Specialist/Technician, AFSC 31255G/75G.		

20 March 1963

Volume I

D2-5859  
4-15.3

241-3-2

POSITION DEFINITION		RECOMMENDED OR AUTHORIZED AFSC AFSC 44250Z/70Z
<u>POSITION NO.</u>	<u>10</u>	<u>POSITION TITLE</u> Missile Pneudraulic Repairman/Repair Technician
<u>GENERAL FEATURES</u>		
<p><b>POSITION SUMMARY:</b>            The Missile Pneudraulic Repairman is responsible for Support Base repair, checkout and testing of the hydraulic equipment components removed from Transporter-Erectors. He is also responsible for assisting the Missile Mechanic/Technician in fault isolating, removing, installing and checking hydraulic equipment components of the Transporter-Erector Tractor and Transporter-Erector Trailer.</p>		
<p>He is responsible for testing and repair of pneudraulic components found in equipment such as:</p> <ul style="list-style-type: none"> <li>1249. Personnel Hatch Installation System</li> <li>1326.2 Blast Door</li> </ul>		
<p>R R R(3)</p>		
<p>He also provides assistance on an "as required" basis to the Electro-Mechanical Team for detailed troubleshooting and repair of pneudraulic components at the Launch Facility and the Launch Control Facility.</p>		
<p><b>ENVIRONMENT:</b>  <b>Work Location:</b> The Missile Pneudraulic Repairman is assigned to the Mechanical Section of the Missile Maintenance Squadron.</p>		

C

20 March 1963

Volume I

D2-5859  
4-25.3

POSITION DEFINITION		RECOMMENDED OR AUTHORIZED AFSC
<u>POSITION N.O.</u>	<u>10</u>	<u>AFSC 44250Z/70Z</u>
<u>POSITION TITLE</u>		
Missile Pneudraulic Repairman/Repair Technician		
ENVIRONMENT: (Cont.)		
Lines of Supervision: He is supervised by the Missile Officer, AFSC 3124G.		
QUALIFICATIONS:		
The perceptual, judgmental and motor skills required for this position are essentially low to medium. For functions such as fault isolation and checkout, these same skills are considered medium to high.		
Task performance is considered critical to Subsystem operations.		
RELATION TO EXISTING AIR FORCE SPECIALTIES:		
This position falls within the scope of AFS Missile Pneudraulic Repairman/Repair Technician, AFSC 44250Z/70Z.		

20 March 1963

Volume I

D2-5859  
4-26.3

M  
C

20 March 1963

**POSITION DEFINITION**

**POSITION  
NO. 12**

**POSITION TITLE  
Missile Facilities Specialist/Technician**

**RECOMMENDED OR  
AUTHORIZED AFSC  
AFSC 54150G/70G**

**GENERAL FEATURES**

**POSITION SUMMARY:**

The Missile Facilities Specialist/Technician is a member of the Missile Team. As a member of this team, he assists in opening and closing the Launch Tube Closure; emplacing and handling environmental covers, personnel cage, safety barriers, and blowers; and assists in preparing the Re-Entry Vehicle - Guidance and Control Van for Missile, Re-Entry Vehicle or Guidance and Control Section removal and replacement.

The Missile Facilities Specialist/Technician is a member of Electro-Mechanical Team and is responsible for the inspecting, servicing, troubleshooting, removal and replacement of equipment and components such as:

1202	G&C Umbilical Retraction Mechanism	
1207	Drier-Air Compressor, Hardened Cable	R
1209.3	Water Control and Removal System, Launcher	R
1210.3	Sewage Disposal System, Launch Control Center	R
1211.3	Environmental Control System, Launcher	R
1212.3	Environmental Control System, Launch Control Center	R
1214	Guidance Section Liquid Cooler	R
1217	Closure, Launcher Tube	R
1230.3	Diesel Fuel Oil System, Launch Control	R
1241.3	Shock Attenuation System, LCC	R
1242.3	Service Lift, Launch Control Facility	R

Volume I

D2-5859  
430.3

2-221-2-4

<u>POSITION NO.</u>	<u>POSITION TITLE</u>	<u>RECOMMENDED OR AUTHORIZED AFSC AFSC 54150G/70G</u>
<u>12</u>	<u>Missile Facilities Specialist/Technician</u>	
	<u>POSITION SUMMARY:</u> (Cont.)	
1249	Hatch Installation, Launcher	R
1280	Launcher Closure Actuating and Locking Mechanism	R
1282	Battery, Emergency Power	R
1288	Battery, Emergency Power	R
1283	Motor Generator Set	R
1318	G&C Cooling Plumbing Set	R(2)
1325.3	Heating System, LCSB	R
1326.2	Blast Door Installation, Launch Control Capsule	R
1330.3	Shock Attenuation System, Launcher Equipment Room Floor	R
1390.3	Ventilation System	R
1418.3	Valve, Blast, 24-Inch	R
1420.3	Damper Set, Sway, Shock Attenuation	R
1421.2	Shock Isolator, Shock Attenuation	R
1443.3	Rail, Hydraulic Pusher	R
1447	Drier, Air Compressor, Hardened Cable	R
	He is assisted in detailed troubleshooting of these equipments by the appropriate AFS having detailed knowledge, such as 44250Z, 54550Y, 54250G or 54350.	
	He performs maintenance and tests at the Launch Facility on the ballistic charge on the	

20 March 1963

Volume I

D2-5859

4-31.3

<u>POSITION DEFINITION</u>	<u>RECOMMENDED OR AUTHORIZED AFSC</u>
<u>POSITION TITLE</u>	<u>AFSC 54150G/70G</u>
<u>POSITION NO.</u> 12	
<u>POSITION SUMMARY:</u> (Cont.) Rotary Actuator Assembly and the Ballistic Gas Generator in the Launch Tube Closure Actuator Mechanism.	
At the Support Base he is responsible for inspection, servicing and referral to the appropriate section in the Maintenance Branch for detailed repair of mechanical Maintenance Ground Equipment, such as: Elevator and Work Cage, Safety Barrier, Truck Dolly, Launcher Closure Tractor, etc.	
<u>ENVIRONMENT:</u>	
<u>Work Location:</u>	He performs his duties and tasks at the Launch Facilities, Launch Control Facilities, and the Support Base.
<u>Lines of Supervision:</u>	As a member of the Mobile Maintenance Teams, his work is coordinated by the Ballistic Missile Analyst Technician, AFSC 31274G. At the Support Base he is supervised by the Missile Officer, AFSC 3124G.
	<u>QUALIFICATIONS:</u>
	The Missile Facilities Specialist/Technician's skill requirements range from low to medium. Medium perceptual skill is required for troubleshooting, inspection, and checkout functions. Medium judgmental skill is required for accomplishing the various detailed maintenance procedures. Medium motor skill is required for installation and removal of assemblies and for aligning and adjusting tasks. Composite-test, checkout, visual check and some non-verifiable repair, installation and servicing functions involve tasks whose performance are critical to subsystem operation but which may affect system operation if not correctly performed.

20 March 1963

Volume I

D2-5859  
4-32.3

**POSITION DEFINITION**

POSITION  
N.O. 12

POSITION TITLE  
Missile Facilities Specialist/ Technician

**RECOMMENDED OR  
AUTHORIZED AFSC  
AFSC 54150G/70G**

**RELATION TO EXISTING AIR FORCE SPECIALTIES:**

This position type falls within the scope of AFS Missile Facilities Specialist/ Technician,  
AFSC 54150G/70G.

20 March 1963

Volume I

D2-5859  
4-33.3

<u>POSITION DEFINITION</u>	<u>RECOMMENDED OR AUTHORIZED AFSC</u>
<u>POSITION TITLE</u>	<u>AFSC 54250G/70G</u>
<u>GENERAL FEATURES</u>	
<b>POSITION SUMMARY:</b>	
The Electrician/Electrical Technician is responsible for maintenance at the Support Base of electrical power source and distribution system components returned from Launch Facilities and Launch Control Facilities. He also provides assistance on an "as required" basis to the Electro-Mechanical Team for detailed troubleshooting and repair of the electrical power system at the Launch Facilities and Launch Control Facilities.	
His duties and tasks include tests to isolate faults to a removable sub-unit, repair by replacing faulty units, and the organizational and field maintenance of such equipment as:	
1209.3 Water Control and Removal System, Elec. Components	R
1242.3 Service Lift, Launch Control Facility	R
1246.3 Cable Assembly Set, Launch Control	R
1248.3 Launcher Intra-Site Cabling	R
1283 Motor Generator	R
1284 Power Supply Group	R
1289 Power Supply Group, LCC	R
1323.3 Electrical Systems, LCC	R
1329.3 Electrical System, Launcher Junction-Box, Main, Launch Facility	R
1337.2 Motor Generator	R
1367.2 Battery Charger Alarm Set Group	R

C

20 March 1963

Volume I

D2-5859  
4-34.3

**POSITION DEFINITION**  
**RECOMMENDED OR  
AUTHORIZED AFSC  
AFSC 5:250G/70G**

**POSITION TITLE**  
**Electrician/Electrical Technician**

**POSITION SUMMARY:** (Cont.)

- 1380      60 Cycle Power Panel
- 1385      Junction Box, Power and Communication - LCC
- 1389. 3    Heating and Ventilating System, LSB
- 1396. 3    Monitoring System, Equipment
- 1415      Fixture, Emergency Lighting and Alarm
- 4024      Semi-Trailer, G&C Re-Entry Vehicle
- 4043      Elevator Work Cage
- 4059      Transporter-Erector Semi-Trailer (Electrical Components)
- 4119      Truck, Transporter-Erector Support
- 4451      Controller, Power Azimuth Drive

**R(3)**  
Checkout, testing and maintaining will be accomplished, using Electrical Power Test Equipment, Battery Chargers, and Standard Electrical Test Equipment.

**ENVIRONMENT:**

**Work Location:**

The Electrician/Electrical Technician's primary duty location is the Maintenance Branch-Mechanical Section at the Support Base and at Launch Facilities and Launch Control Facilities when serving as a member of the Electro-Mechanical Team.

At the Support Base he is supervised by the Missile Officer, AFSC 3124G. When acting as a member of the Electro-Mechanical Team, his work is coordinated by the Ballistic Missile Analyst Technician, AFSC 31274G.

b6

20 March 1963

Volume I

D2-5859  
4-35.3

<u>POSITION NO.</u>	<u>POSITION DEFINITION</u>	<u>RECOMMENDED OR AUTHORIZED AFSC</u>
<u>POSITION N.O. 13</u>	<u>Electrician/Electrical Technician</u>	<u>AFSC 54250G/70G</u>
<u>QUALIFICATIONS:</u>		
The duties and tasks of the Electrician/Electrical Technician involve low to medium perceptual, judgmental and motor skills.		
Task performance is generally critical to subsystem operation.		
<u>RELATION TO EXISTING AIR FORCE SPECIALTIES:</u>		
This position type falls within the scope of AFS Electrician/Electrical Technician, AFSC 54250G/70G.		

20 March 1963

Volume I

D2-5859  
4-36.3

1C

POSITION NO.	POSITION DEFINITION	RECOMMENDED OR AUTHORIZED AFSC
15	Refrigeration Specialist/Technician	AFSC 54550Y/70Y
<u>GENERAL FEATURES</u>		

POSITION SUMMARY:

The Refrigeration Specialist/Technician is responsible for support maintenance of the following: Environmental Control and Equipment Cooling components returned from Launch Facilities and Launch Control Facilities, Maintenance Ground Equipment Cooling Units used at the Support Base, and Transporter-Erector Environmental Control System components. He also provides back-up assistance on an "as required" basis to the Electro-Mechanical Team.

His duties and tasks include tests to isolate faults to a removable sub-unit, repair by replacing faulty units, and organizational and field maintenance of equipment such as:

603.2	Environmental System, C24 (Missile Targeting Set)	R
1211.3	Environmental System, Launch Facility	R
1212.3	Environmental System, Launch Control Facility	
1214	Cooling Unit, Guidance and Control Compartment	
1318	Guidance and Control Cooling Plumbing Set	
3035	Test Set, Cooling Liquid, Guidance and Control	
4024	Environmental System, R/V-G&C Van	
4059	Environmental System, Transporter-Erector	
4075	Environmental System, Transporter-Erector	
4115	Environmental Control, Auxiliary	
4150	Test Bench, Guidance and Control Ground Cooling	
4191	Tank, Liquid Storage, Metal	

20 March 1963

Volume I

D2-5859  
4-39.3

POSITION DEFINITION		RECOMMENDED OR AUTHORIZED AFSC AFSC 54550Y/70Y
<u>POSITION NO.</u>	<u>POSITION TITLE</u>	
<u>15</u>	<u>Refrigeration Specialist/Technician</u>	
<u>POSITION SUMMARY:</u> (Cont.)		
1390.3 Ventilation System, LCSB		
1436.3 Ventilation System LCEB		
Checkout and testing is accomplished using such equipment as a Multimeter, Refrigeration Repair Kit, Thermometer, Air Flow meters, and hand tools.		
<u>ENVIRONMENT:</u>		
The Refrigeration Specialist/Technician's primary duty is at the Maintenance Branch-Mechanical Section at the Support Base and at Launch Facilities and Launch Control Facilities when required as a member of the Electro-Mechanical Team.		
<u>Lines of Supervision:</u>		
At the Support Base he is supervised by the Missile Officer, AFSC 3124G. When acting as a member of Electro-Mechanical Team, his work is coordinated by the Ballistic Missile Analyst Technician, AFSC 31274G.		
<u>QUALIFICATIONS:</u>		
The duties and responsibilities of the Refrigeration Specialist/Technician require medium perceptual and motor skills; and high to medium judgmental skill in fault isolating and testing functions. Task performance is generally critical to subsystem operation.		
<u>RELATION TO EXISTING AIR FORCE SPECIALTIES:</u>		
The duties of this position fall within the scope of AFS Refrigeration Specialist/Technician, AFSC 54550Y/70Y.		

20 March 1963

Volume I

D2-5859

4-40.3

WING III MINUTEMAN DIRECT SUPPORT MANNING SUMMARY																		
Recommended Team and Composition	No. of Teams	3124G	30452	31254G	31255G	31256G	33150B	36151	36152	44250Z	44350G	54150G	54250C	54350	54550Y	60350B	X3XXX	
Missile Team	9																	
1-31254G																		
2-33150B																		
1-44350G																		
1-54150G																		
Transport. & Handling Team	3																	
1-44350G																		
3-60350B																		
Alignment & Targeting Team	8																	
1-3124G																		
1-31254G																		
1-44350G																		
Electro- #1 Mechanical	5																	
1-31254G																		
1-54150G																		
1-XXXXXX																		
Electro- #2 Mechanical	2																	
1-31254G																		
1-54150G																		
1-54250G																		
Electro- #3 Mechanical	1																	
1-31254G																		
1-54150G																		
1-54550Y																		
Electro- #4 Mechanical	1																	
1-31254G																		
1-54150G																		
1-36152																		
Electro- #5 Mechanical	2																	
1-31254G																		
1-54150G																		
1-54350																		
Electro- #6 Mechanical	1																	
1-31254G																		
1-54150G																		
1-44350G																		
Electro- #7 Mechanical	5																	
1-31254G																		
1-54150G																		
1-30452																		
HCS Team	2																	
5-36151																		
AFSC		3124G	30452	31254G	31255G	31256G	33150B	36151	36152	44250Z	44350G	54150G	54250G	54350	54550Y	60350B	XXXXXX	
MOBILE MAINTENANCE SUB-TOTAL	8	5	34					18	10	1	21	26	2	2	1	9	5	142
SUPPORT BASE MAINTENANCE SUB-TOTAL	5	1	5	1	3	11	3	1	1	1	1	3		1				37
TOTAL MAN MONTHS MAINTENANCE BY AFSC	13	6	39	1	3	29	13	2	1	22	27	5	2	2	9	5	179	
MISSILE COMBAT CREW (AFSC 1825G)														150				
GRAND TOTAL														329				

20 March 1963

TABLE 5-2.3

Volume I

D2-5859  
5-9.3

**WING III**  
**MINUTEMAN MOBILE MAINTENANCE TEAMS**

<u>Team Composition by AFSCs</u>			<u>AFSC</u>	<u>Title</u>
<u>Team</u>	<u>No.</u>	<u>AFSC</u>		
Missile Team	1	312X4G	3124G	Missile Officer
	2	331X0B	312X4G	Ballistic Missile Analyst Specialist/Technician
	1	443X0G	331X0B	Nuclear Weapons Specialist
	1	541X0G		
Transport & Handling	1	443X0G	304X2	Ground Communications Equip. Repairman/Tech.
	3	603X0B		
Alignment & Targeting	1	3124G	361X2	Telephone Installer Repair- man
	1	312X4G	443X0G	Missile Mechanic/Maint- enance Technician
	1	443X0G	541X0G	Missile Facilities Special- ist/Technician
Electro-Mech. No. 1	1	312X4G	542X0G	Electrician/Electrical Tech.
	1	541X0G	543X0	Electrical Power Production Specialist/Technician
	1	XXXXXX	545X0Y	Refrigeration Specialist/ Technician
Electro-Mech. No. 2	1	312X4G	603X0B	Vehicle Operator/Motor Transportation Supervisor
	1	541X0G		
	1	542X0G	361X1	Cable Splicer/Cable Splic- ing Technician
Electro-Mech. No. 3	1	312X4G		
	1	541X0G		
	1	545X0Y		
Electro-Mech. No. 4	1	312X4G		
	1	541X0G		
	1	361X2		
Electro-Mech. No. 5	1	312X4G		
	1	541X0G		
	1	543X0		
Electro-Mech. No. 6	1	312X4G		
	1	541X0G		
	1	443X0G		
Electro-Mech. No. 7	1	312X4G		
	1	541X0G		
	1	304X2		
Hardened Cable System Team	5	361X1		

 The Electro-Mechanical Teams are numbered 1 through 7. Each E-M Team has a minimum of three (3) people and each team has a 312X4G and a 541X0G. E-M Team No. 1 has any of the other AFSCs available for the third person. E-M Teams No. 2 through 7 have a specific AFSC for the third man, depending on what job is to be done.

TABLE 5-2B.3

March 20, 1963

Volume I D2-5859  
5-5A.3

## TEAM COMPOSITION COMPANION CHART

20 March 1963

Team Composition by AFSCs		WING I		WING II		WING III	
Recommended	No. on Team	Team Name	AFSC	Recommended	No. of Teams	Recommended	No. of AFSCs Recommended
Middle Team	1	312X4G	20	20	12	12	9
	2	331X08	40	40	24	24	10
	1	443X0G	20	20	12	12	9
	1	541X0G	20	20	12	12	9
Transport & Handling	1	443X0G	8	8	4	4	3
	3	603X08	24	24	12	12	9
Alignment & Targeting	1	312X4G	14	14	12	12	8
	1	312X4G	14	14	12	12	8
	1	443X0G	14	14	12	12	8
Electro-Mech.	1	312X4G	15	15	8	8	5
No. 1	1	541X0G	15	15	8	8	5
		XXX0XX	15	15	8	8	5
Electro-Mech.	1	312X4G	5	5	2	2	2
No. 2	1	541X0G	5	5	2	2	2
		542X0G	5	5	2	2	2
Electro-Mech.	1	312X4G	2	2	2	2	1
No. 3	1	541X0G	2	2	2	2	1
		545X0Y	2	2	2	2	1
Electro-Mech.	1	312X4G	2	2	2	2	1
No. 4	1	541X0G	2	2	2	2	1
		361X2	2	2	2	2	1
Electro-Mech.	1	312X4G	1	1	1	1	1
No. 5	1	541X0G	1	1	1	1	1
		543X0	1	1	1	1	1
Electro-Mech.	1	312X4G	1	1	1	1	1
No. 6	1	541X0G	1	1	1	1	1
		443X0G	1	1	1	1	1
Electro-Mech.	1	312X4G	6	6	7	7	5
No. 7	1	541X0G	+	+	7	7	5
		304X2	12	12	7	7	5
Hardened Cable System Team	5	361X1	2	10	2	10	10
		TOTALS	76	280	53	53	39

△ Includes loading for 100% of HF/UHF failures.

Wing 1 requires a team consisting of One (1) 3/2X10 and Two (2) 10x12's.

WING ICalculated  
Loading

Position	AFSC	Title		
1	1825G/1816	Missile Launch Officer/Missile Operations Staff Officer	150	1421.
2	3124G/3116	Missile Officer/Missile Staff Officer	19	
3	304X2	Ground Communications Equipment Repairman (Light)/ Tech.	13	2900, 2906, 2950,
4	312X4G	Ballistic Missile Analyst Specialist/Technician	71	602.2
5	312X5G	BM Checkout Equipment Specialist/Technician	1	717.2
6	312X6G	BM Launch Equipment Repairman/ Technician	6	603.2
7	331X0B	Nuclear Weapons Specialist/ Technician	51	
8	361X1	Cable Splicer/Cable Splicing Technician	13	
9	361X2	Telephone Installer-Repairman/ Installation and Repair Super.	3	
10	442X0Z	Missile Pneudraulic Repairman/ Technician	1	
11	443X0G	Missile Mechanic/Maintenance Technician	44	
12	541X0G	Missile Facilities Specialist/ Technician	47	1324. 1418. 1211.
13	542X0G	Electrician/Electrical Tech.	9	
14	543X0	Electrical Power Production Specialist/Technician	1	
15	545X0Y	Refrigeration Specialist/ Tech.	3	603.2
16	603X0B	Vehicle Operator/Motor Transportation Supervisor	24	
		Unspecified AFSC	15	

WING MANNING TOTAL

471

1

MANNING COMPARISON CHARTWING II

New Equipment by Figure A No.	Deleted Equipment by Figure A No.	Calculated Loading	
1421.2		150	
		17	
2900, 2901, 2902, 2903, 2904, 2905, 2906, 2907, 2908, 2909, 2910, 2911, 2950, 2952, 2958	1293, 1295, 1296, 1411, 3109	8	
602.2, 604.2, 717.2	602, 604, 717, 1411	52	
717.2, 3007.2	717, 3007	1	3007
603.2	603	3	
		33	
		13	
		3	
		1	
		30	
1324.2, 1323.2, 1390.2, 1417.2, 1418.2, 1212.2, 1240.2, 1421.2, 1211.2, 1405.2, 1242.2	1323, 1324, 1390, 1211, 1405, 1212, 1242	36	1209.3, 1210.3, 1211.3, 1242.3, 1390.3, 1440.3, 1450.3, 1432.3
		5	1323.3, 1396.3, 1437.3,
		1	
603.2	603	3	1211.3, 1212.3
		12	
		8	

CHART 9-2-1

WING III

3

New Equipment  
By Figure A No.

3007

3007.4

1209.3, 1210.3, 1211.3, 1405.3, 1429.3, 1441.3, 1323.3, 1443.3, 1212.3, 1230.3,  
1242.3, 1390.3, 1396.3, 1241.3, 1325.3, 1330.3, 1428.3, 1436.3, 1439.3,  
1140.3, 1450.3, 1432.3

1209.2, 1211.2, 1439.2, 1390.2, 1396.2

1323.3, 1396.3, 1437.3, 1209.3, 1242.3, 1246.3, 1248.3, 1329.3, 1389.3

1249.4, 1405.2, 1246.2, 1248.2

1211.3, 1212.3

1211.2, 1212.2

CHART 5-2.3

20 March 19

WING IIIDeleted Equipment  
by Figure A No.Calculated  
Loading

		150
		13
		6
		39
3Q07. 2		1
		3
		29
		13
		2
		1
		22
, 1443. 3, 1212. 3, 1230. 3, , 1428. 3, 1436. 3, 1439. 3, , 1329. 3, 1389. 3	1209. 2, 1210. 2, 1405. 2, 1230. 2, 1396, 1241. 2, 1283, 1211. 2, 1417. 2, 1212. 2, 1242. 2, 1323. 2, 1324. 2, 1390. 2, 1383, 4141, 4282, 1325. 2, 1330 1249, 4105, 4166, 1323. 2, 1396, 1209. 2, 1242. 2, 1246. 2, 1248, 1329. 2, 1389. 2	27 5 2
		9
		5
		329

Volume I

D2-4459

20 March 1963



8A	8B	9A	9B	9C	9D	9E	10A	10B	10C	11A	11B	11C	12A	12B	12C	12E
.2 1337.2 <u>1201</u>	1412.2 <u>1201</u>	G&C <u>1284</u>	G&C	G&C	604.2 1201	1412.2 1201	G&C D 604.2 <u>1201</u>	D 1282 <u>1284</u> <u>1379.2</u>	1412.2 1201	1214 1318	G&C	1412.2 1201	604.2	604.2	604.2	1412. 1201
<u>D</u> <u>1201</u>		<u>1201</u> <u>604.2</u>		<u>1201</u>						<u>G&amp;C</u> <u>1337.2</u> <u>1201</u>	<u>1201</u>		<u>G&amp;C</u> <u>1201</u>			
<u>9.7</u>		431.1	47.4	30.8			77.9	318.8		<u>4.5</u>	5.1		<u>37.5</u>			
<u>7.0</u>							12.5	211.2								
<u>2.2</u>		80.0	10.9	6.9			16.6	65.2		<u>1.0</u>	1.1		<u>8.6</u>			
<u>.1</u>	.8	<u>7.8</u>		<u>.2</u>	.7	.8	<u>.1</u>		.8	<u>.1</u>	<u>.1</u>	.8	37.5	1.6	1.2	.8
								<u>13.2</u>				<u>54.5</u>				
<u>7.8</u>										<u>1.8</u>						

3



5

## **ORGANIZATIONAL MAINTENANCE AT LAUNCH FACILITY**

6

**TABLE 5-3. 3**

WING III

## LAUNCH FACILITY FAILURE INDICATIONS

7

	III B	IV	V	VI	VII	VIII	IX A	IX B	X A	X B	X I	X II	X III	X IV	X V	X VI	X V I	
4 1 8 8 2	1251	1228	G&C 604.2 1201	1201	604.2	1228 1251	1201	1251 1201	1201	1201	1201	1337.2	604.2 1251 1201 1209.3 1211.3 1228 1251	1303 <u>1251</u>	1201	1201	1228	1201
			42.7										20.2	1268 1284 1331.3 1337.3 1412.2 2900 2903 G&C 1329.3 D				
			8.6										3.7	4.6				
	6.6	.2		.2	1.5	45.0	23.5	1.7	2.2	.1	1.0		100.4	1.9	.2	1.8	3.	
													17.3					
													7.8					
													18.8					
													117.7					
													65.1	1.0				
													10.0					

ONS

7

8

XVI	XVII	XVIII	XIX	XX	XXI	XXII	XXIII	XXIV	XXV	XXVI	XXVII	XXVIII	XXIX	XXX	XXXI		
201 228	1201 1228	1228	1228	1228	1201	1201	1201	1201	1201	1201	2900 2905	2910 2911	1331.3	2900 1331.3	2910 2911 1311.3		
													1251			Unmonitored Faults LF	
																5.7	
																1	
																0	
.8	3.1	2.7	3.6	.1	1.4	.2	.2	.1	.1	1.8			.7			111.7	
													.1			3.9	
																4.3	
													6.5	.6	6.9	4.4	10.5

All figures in matrix indicate hours per month per team.  
 Second Trip hours are underlined.  
 Hold Over hours are enclosed in cartouch.

20 March 1963

XXIII	XXIV	XXV	XXVI	XXVII	XXVIII	XXIX	XXX	XXXI				NUMBERS OF TEAMS FOR LF
1201	1201	1201	1201	2900 2905	2910 2911	1331.3 1251	2900 1331.3	2910 2911 1311.3	Unmonitored Faults LF	TOTAL TEAM HOURS/MONTH FOR LF		
									5.7	R/V Scheduled Sampling 55.7	8.3	
										TOTAL 1165.5		
										Missile Handling SMSA 166.1	2.9	
										TOTAL 400.5		
										Periodic Mirror Check 674.8	7.6	
										Operational Retargeting 152.7		
										TOTAL 1069.8		
.2	.1	.1	1.8			.7			111.7	552.0	3.9	
						(.1)				127.9	0.9	
										123.2	0.9	
									3.9	22.7	0.2	
										138.2	1.0	
									4.3	89.3	0.6	
									10.5	69.2	0.5	

Figures in matrix indicate hours per month per team.  
and Trip hours are underlined.  
Over hours are enclosed in cartouch.

## WING III

## ORGANIZATIONAL MAINTENANCE AT LAUNCH CONTROL FACILITY

	OGE	RPIE	Total Team Hours / Month	Number of Teams
Electro - #1 Mechanical				
1 - 31254G 1 - 54150G 1 - XXXXX	69.3	28.8	98.1	.7
Electro - #2 Mechanical				
1 - 31254G 1 - 54150G 1 - 54250G	4.8	17.3	22.1	.2
Electro - #3 Mechanical				
1 - 31254G 1 - 54150G 1 - 54550Y	3.5		3.5	
Electro - #4 Mechanical				
1 - 31254G 1 - 54150G 1 - 36152	38.4		38.4	.3
Electro - #5 Mechanical				
1 - 31254G 1 - 54150G 1 - 54350G		8.9	8.9	.1
Electro - #7 Mechanical				
1 - 31254G 1 - 54150G 1 - 30452	603.6		603.6	4.3
HCS Team 5 - 36151			195.9	1.4

Note: Work on the Hardened Cable System (HCS) may be conducted at the LCF, LF, or between them

Table 5-4.3

March 20, 1963

Volume I D2-5859  
5-7.3

## MAINTENANCE AT THE SUPPORT BASE

AFSC	OGE MAINT.	RPIE MAINT.	MGE MAINT.	R/V & R/V MGE MAINT.	MCC OPERATION	CABLE PLANT IN PLACE		TOTAL SUPPORT BASE MAINT. MAN/ MONTHS
						RECORDS	MAINT.	
3124G					5.00			5
30452	0.27		0.01					1
31254G					4.22			5
31255G								1
31256G	1.81		0.58					3
33150B					11.0			11
36151						3.0	3	
36152	0.6							1
44250Z					0.43			1
44350G						0.51		1
54150G						0.34		1
54250G	1.88		0.12			0.39		3
54550Y	0.16		0.05			0.18		1

20 March 1963

Volume I

D2-5859  
5-8.3

Note: Figures show men per month.

TABLE 5-5.3